

Environmental Product Declaration

In accordance with 14025 and EN15804 +A2

PAROC LT Produced Stone Wool Thermal Insulation



Owner of the declaration:
Paroc Group Oy

Product name:
PAROC LT Produced Stone Wool Thermal
Insulation

Declared unit:
1 m² of stone wool with a thermal resistance of
1 m²K/W.

Product category /PCR:
CEN Standard EN 15804+A2 serves as core
PCR. NPCR PART A Construction Products and
Services NPCR 012 Part B for Thermal
Insulation Products.

Program holder and publisher:
The Norwegian EPD foundation

Declaration number:
NEPD-4339-3565-EN

Registration number:
NEPD-4339-3565-EN

Issue date: 05.04.2023

Valid to: 05.04.2028

Updated 04.03.2024



General information

Product:

PAROC LT Produced Stone Wool Thermal Insulation

Program Operator:

The Norwegian EPD Foundation
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Tlf: +47 23 08 80 00
e-mail: post@epd-norge.no

Declaration Number:

NEPD-4339-3565-EN

This declaration is based on Product

Category Rules:

CEN Standard EN 15804+A2 serves as core PCR. NPCR PART A Construction Products and Services NPCR 012 Part B for Thermal Insulation Products.

Statements:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer, life cycle assessment data and evidence.

Declared unit:

1 m² of stone wool with a thermal resistance (R) of 1 m²K/W.

Declared unit with option:

Functional unit:

1 m² of stone wool with thermal resistance (R) of 1 m²K/W. 1 m² of the reference product, PAROC Ultra, at R=1 is at a weight of 1,15 kg. The impact excludes any lamination.

Verification:

Independent verification of the declaration and data, according to ISO14025:2010

internal external



Martin Erlandsson, IVL

Independent verifier approved by EPD Norway

Owner of the declaration:

Paroc Group Oy
Contact person: Emelia Samuelsson
Phone: +358 46 876 8000
e-mail: InsulationEurope.Sustainability@owenscorning.com

Manufacturer:

Paroc Group Oy
FI-00181, Helsinki, Finland
Phone: +358 46 876 8000
e-mail: InsulationEurope.Sustainability@owenscorning.com

Place of production:

Vilnius, Lithuania

Management system:

ISO 9001 and ISO 14001

Organisation no:

887294852

Issue date:

05.04.2023

Valid to:

05.04.2028

Year of study:

2021

Comparability:

EPDs from other programmes than EPD Norway may not be comparable.

The EPD has been worked out by:

Emelia Samuelsson, Owens Corning

Emelia Samuelsson  **PAROC**[®]

Approved



Manager of EPD Norway

Product

Product description:

PAROC® stone wool insulation is naturally non-combustible and durable. It is made of natural stone (~98%) and air (~2%). As stone wools thermal performance is based on static air, insulation products keep their energy saving abilities and dimensions in different temperature and moisture conditions during the life cycle of a building.

The products covered by this declaration are PAROC stone wool thermal insulation products manufactured in Vilnius, Lithuania using cupola furnaces.

Product specification:

The average composition used for this EPD is calculated based on line consumption figures for raw materials. The raw materials are mainly natural stones and resin binder.

Materials	%
Stone Wool Fiber	>94
Binder (phenol-formaldehyde-urea-copolymer)	<6
Dustbinding (mineral oil)	<1

Technical data:

For the products covered by this EPD, the performance data are in accordance with the declaration of performance with respect to its essential characteristics according to EN 13162:2012+A1:2015, "Thermal insulation products for buildings – Factory made mineral wool (MW) products – Specification."

- Thermal conductivity: 0,033-0,044 W/mK, EN 12939 and EN 12667
- Fire class: A1, EN 13501-1:2007+A1:2009

Complete technical specifications can be found on www.paroc.com

Market:

This EPD is intended for the markets that receives PAROC building insulation products from the factory in Vilnius, Lithuania. Those markets are mainly Lithuania, Latvia, Estonia, Poland and Ukraine.

Reference service life, product:

The reference service life of PAROC products is equal to the reference service life of the building. For the purpose of this EPD the reference service life is considered to be minimum 60 years, which is usually the assumption about the lifetime of the building where this is installed.

Reference service life, building:

The reference service life of a building is set to 60 years in this EPD.

LCA: Calculation rules

Declared unit:

The declared unit refers to 1 m² of PAROC Ultra with a thermal resistance (R) of 1 m²K/W, thickness of 35 mm and weight of 1,15 kg.

The specific product, PAROC Ultra, is a stone wool slab with a density of 32,8 kg/m³ and thickness of 100 mm.

The impact indicators for another product can be calculated by multiplying the results of the EPD with the respective scaling factor for the products covered by this EPD. A table with the products available in the scaling table and their respective scaling factors is provided within the 'Additional technical information' section.

Data quality:

All primary data are collected line specific, based on the financial year 2021. The production data from Vilnius involves production lines with cupola furnaces.

The background data has been taken from the latest available GaBi database (/GaBi TS) CUP 2022.2. The requirements for data quality and background data correspond to the specifications of EN 15804+A2. The process data and the used background data are consistent.

The data quality can be qualified as good.

Allocation:

The allocation correspond to the specifications of EN 15804+A2. Allocation and other methodological choices are made consistently throughout the model. As a worst-case approach, price allocation is considered for the plant.




Figure 1. Schematic representation of the LCA system boundaries for the production module (A1-A3)




Figure 2. Schematic representation of the LCA system boundaries for the construction process stage (A4-A5)




Figure 3. Schematic representation of the LCA system boundaries for the End-of-life stage (C1-C4)




Figure 4. Schematic representation of the LCA system boundaries for the benefits and loads beyond the product system boundary in module D

System boundary:

The system boundary of the EPD follows the modular structure defined by EN15804+A2. The flowchart above represents the system boundaries for the product, construction process, end-of-life and benefits (D). The use stage (B1-B7) relating to the building site is not included in this study, as there are no activities and no significant environmental impact in the use stage.

Cut-off criteria:

All data from the production data acquisition has been considered, i. e. all basic materials used per formulation, utilized thermal energy, internal fuel consumption and electric power consumption, direct production waste, and all emission measurements available. All material and energy flows, except paper for labels in packaging, with a proportion of less than 1% have been considered. The neglected flow (paper label for packaging) does not exceed 1% of the impact categories. Machines and facilities required during production are neglected.

The declared unit of stone wool is without any coating.

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD. There are no maintenance (B2), repair (B3), replacements (B4) or refurbishments (B5) required during the use of PAROC stone wool thermal insulation products in standard conditions. They do not require energy (B6) or water (B7) during their operational life. No significant emissions to the indoor environment occur in module (B1). Therefore, modules B1-B7 are not relevant for this EPD.

Transport from production place to assembly/user (A4)

Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance KM	Fuel/Energy consumption (l/t.km)	value (l/t for total distance)
Truck	30	Truck, Euro 5, 27 t payload	120	0,006	0,72

The A4 distance is calculated as average distance for the Lithuanian market.

Assembly (A5)

	Unit	Value
Auxiliary	kg	0,00
Water consumption	m ³	0,00
Electricity consumption	kWh	0,00
Other energy carriers	MJ	0,00
Material loss	kg	0,02
Output materials from waste treatment	kg	0,08
Dust in the air	kg	0,00

The installation in general takes place manually. Thus, machines or energy expenditures are not taken into account. Most products are self-supporting and do not need support. Installation losses have been accounted for 2% as a conservative approach. Within module A5 a site related packaging waste processing is included in the LCA. It is assumed that packaging material as leftover of the installed product is for 100% collected and incinerated.

End of Life (C1, C3, C4)

	Unit	Value
Hazardous waste disposed	kg	0,00
Collected as mixed construction waste	kg	0,00
Reuse	kg	0,00
Recycling	kg	0,00
Energy recovery	kg	0,00
To landfill	kg	1

Although mineral wool products from Paroc can be recycled, they are estimated as being 100% landfilled after the use phase as the most conservative approach.

Transport to waste processing (C2)

Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance KM	Fuel/Energy consumption (l/t.km)	value (l/t for total distance)
Truck	50	Truck, Euro 5, 27 t payload	50	0,006	0,30

The distance represents an average distance to landfill, the stone wool is in general not transported alone to landfill, therefore a load factor of 50% is considered in this case.

Benefits and loads beyond the system boundaries (D)

Benefits are considered in module D for the thermal and electrical energy, generated in module A5, due to thermal treatment of packaging waste (polyethylene film and wooden pallets) after installation.

Additional technical information

Below a list of products covered by this EPD and their scaling factors. The scaling factor can be used to estimate the environmental performance indicators for the specific products of 1 m² when R=1. The environmental performance solely refer to the stone wool, and thus do not include the environmental performance of any potential coatings. Due to this fact, the variation is less than 10% by reason of the density, lambda and binder. The scaling calculation shall be done as follows:

Reference product environmental impact per m² (1,31) x scaling factor of specific product (1,00)

Product Group	Product Name	Unit	Value
Flexible Slabs & Mats	PAROC Ultra (42-200 mm thickness, lambda 0,035, average density 32,8 kg/m ³)	1 m ²	1,00
Flexible Slabs & Mats	PAROC Ultra plus (50-200 mm thickness, lambda 0,034, average density 42 kg/m ³)	1 m ²	1,24
Flexible Slabs & Mats	PAROC Solid (50-180 mm thickness, lambda 0,037, average density 29,9 kg/m ³)	1 m ²	0,96
Flexible Slabs & Mats	PAROC Sonus (75-100 mm thickness, lambda 0,044, average density 24 kg/m ³)	1 m ²	0,92
Roofs	PAROC ROS 30 (50-200 mm thickness, lambda 0,036, average density 96 kg/m ³)	1 m ²	3,01
Roofs	PAROC ROS50 (40-150 mm thickness, lambda 0,038, average density 123,5 kg/m ³)	1 m ²	4,09
Roofs	PAROC ROS60 (40-50 mm thickness, lambda 0,039, average density 130 kg/m ³)	1 m ²	4,42
Roofs	PAROC ROS70 (40-150 mm thickness, lambda 0,039, average density 136 kg/m ³)	1 m ²	4,62
Roofs	PAROC ROL 30 (170-360 mm thickness, lambda 0,038, average density 65 kg/m ³)	1 m ²	2,15
Roofs	PAROC ROB50 (20-30 mm thickness, lambda 0,037, average density 156,5 kg/m ³)	1 m ²	5,04
Roofs	PAROC ROB60 (t) (20-30 mm thickness, lambda 0,038, average density 173 kg/m ³)	1 m ²	5,73
Roofs	PAROC ROB80 (t) (20-30 mm thickness, lambda 0,038, average density 186 kg/m ³)	1 m ²	6,16
Roofs	PAROC ROB100 (30-50 mm thickness, lambda 0,039, average density 188,5 kg/m ³)	1 m ²	6,40

Special Applications	PAROC SSB1 (20-50 mm thickness, lambda 0,035, average density 117,5 kg/m ³)	1 m ²	3,58
Special Applications	PAROC SSB2 (t) (30 mm thickness, lambda 0,037, average density 167,5 kg/m ³)	1 m ²	5,40
Special Applications	PAROC FPS14 (30-100 mm thickness, lambda 0,037, average density 138 kg/m ³)	1 m ²	4,45
Special Applications	PAROC FPS17 (20-50 mm thickness, lambda 0,038, average density 170 kg/m ³)	1 m ²	5,63
Special Applications	PAROC CGL 20 cy (50-400 mm thickness, lambda 0,037, average density 60 kg/m ³)	1 m ²	1,93
Special Applications	PAROC GRS 20 (40-200 mm thickness, lambda 0,035, average density 96,5 kg/m ³)	1 m ²	2,94
Facade	PAROC COS 5 (40-200 mm thickness, lambda 0,035, average density 60 kg/m ³)	1 m ²	1,83
Facade	PAROC WAS 25 (t) (tb) (30-50 mm thickness, lambda 0,033, average density 88 kg/m ³)	1 m ²	2,53
Facade	PAROC WAS 35 (t) (tb) (30-200 mm thickness, lambda 0,033, average density 70 kg/m ³)	1 m ²	2,01
Facade	PAROC WAS 50 (t) (tb) (50-200 mm thickness, lambda 0,034, average density 45 kg/m ³)	1 m ²	1,33
Facade	PAROC WAB 10t (20 mm thickness, lambda 0,036, average density 150 kg/m ³)	1 m ²	4,70
Facade	PAROC Linio 10 (cc) (50-200 mm thickness, lambda 0,036, average density 81,5 kg/m ³)	1 m ²	2,56
Facade	PAROC Linio 15 (50-180 mm thickness, lambda 0,037, average density 100,5 kg/m ³)	1 m ²	3,24
Facade	PAROC Linio 15 (30 mm thickness, lambda 0,037, average density 125 kg/m ³)	1 m ²	4,03
Facade	PAROC Linio 15 (30 mm thickness, lambda 0,037, average density 125 kg/m ³)	1 m ²	4,03
Facade	PAROC Linio 80 (50-340 mm thickness, lambda 0,040, average density 78 kg/m ³)	1 m ²	2,72
Facade	PAROC Linio Pro (50-240 mm thickness, lambda 0,034, average density 86 kg/m ³)	1 m ²	2,55
Facade	PAROC Tutto (t) (tb) (45-250 mm thickness, lambda 0,033, average density 70 kg/ m ³)	1 m ²	2,01
Facade	PAROC Tutto (t) (tb) (30 mm thickness, lambda 0,033, average density 80 kg/ m ³)	1 m ²	2,30

LCA: Results

The system boundary of the EPD follows the modular structure defined by EN15804+A2. The table identifies the modules included in this study. The use stage (B1-B7) relating to the building site is not included in this study, as there are no activities and no significant environmental impact in the use stage.

System boundaries (X=included, MND= module not declared, MNR=module not relevant)

Product stage			Assembly stage		Use stage								End of life stage				Benefits & loads beyond system boundary
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential	
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
X	X	X	X	X	MNR	MNR	MNR	MNR	MNR	MNR	MNR	X	X	X	X	X	

Core environmental impact indicators

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-total	kg CO2 eq.	1,31E+00	2,97E-03	1,70E-01	1,19E-02	3,60E-03	0	1,55E-02	-5,85E-02
GWP-fossil	kg CO2 eq.	1,40E+00	2,93E-03	7,39E-02	1,18E-02	3,56E-03	0	1,54E-02	-5,82E-02
GWP-biogenic	kg CO2 eq.	-9,44E-02	0	9,60E-02	1,06E-04	2,26E-05	0	5,97E-05	-2,98E-04
GWP-LULUC	kg CO2 eq.	2,67E-04	1,64E-05	6,29E-06	2,49E-06	1,97E-05	0	2,85E-05	-6,41E-06
ODP	kg CFC11 eq.	8,82E-13	1,77E-16	2,81E-14	1,72E-13	2,11E-16	0	3,62E-14	-3,94E-13
AP	mol H ⁺ eq.	3,05E-03	2,46E-06	8,25E-05	2,58E-05	1,20E-05	0	1,09E-04	-7,66E-05
EP-freshwater	kg P eq.	7,86E-07	8,80E-09	1,80E-08	3,43E-08	1,05E-08	0	2,61E-08	-8,02E-08
EP-marine	kg N eq.	6,73E-04	7,03E-07	1,98E-05	5,79E-06	5,58E-06	0	2,80E-05	-2,08E-05
EP-terrestrial	mol N eq.	1,19E-02	8,54E-06	3,36E-04	6,08E-05	6,23E-05	0	3,07E-04	-2,22E-04
POCP	kg NMVOC eq.	1,75E-03	2,12E-06	5,17E-05	1,57E-05	1,08E-05	0	8,49E-05	-5,81E-05
ADP-M&M	kg Sb eq.	6,76E-08	2,46E-10	1,55E-09	3,20E-09	2,95E-10	0	1,58E-09	-8,79E-09
ADP-fossil	MJ	1,32E+01	3,94E-02	2,76E-01	2,13E-01	4,71E-02	0	2,02E-01	-9,89E-01
WDP	m ³	3,71E-02	2,64E-05	1,68E-02	2,68E-03	3,16E-05	0	1,69E-03	-6,21E-03

GWP-total: Global Warming Potential; **GWP-fossil:** Global Warming Potential fossil fuels; **GWP-biogenic:** Global Warming Potential biogenic; **GWP-LULUC:** Global Warming Potential land use and land use change;

ODP: Depletion potential of the stratospheric ozone layer; **AP:** Acidification potential, Accumulated Exceedance; **EP-freshwater:** Eutrophication potential, fraction of nutrients reaching freshwater end compartment; See “additional requirements” for indicator given as PO4 eq. **EP-marine:** Eutrophication potential, fraction of nutrients reaching freshwater end compartment; **EP-terrestrial:** Eutrophication potential, Accumulated Exceedance; **POCP:** Formation potential of tropospheric ozone; **ADP-M&M:** Abiotic depletion potential for non-fossil resources (minerals and metals); **ADP-fossil:** Abiotic depletion potential for fossil resources; **WDP:** Water deprivation potential, deprivation weighted water consumption

Reading example: $9,0 \text{ E-}03 = 9,0 \cdot 10^{-3} = 0,009$

Additional environmental impact indicators

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PM	Disease incidence	1,61E-07	2,49E-11	3,10E-09	2,14E-10	6,36E-11	0	1,61E-07	2,49E-11
IRP	kBq U235 eq.	3,24E-02	7,13E-06	9,81E-04	5,78E-03	8,53E-06	0	0,032444	7,13E-06
ETP-fw	CTUe	2,93E+00	2,73E-02	6,34E-02	9,35E-02	3,27E-02	0	2,934068	0,027343
HTP-c	CTUh	5,68E-10	5,51E-13	1,24E-11	2,68E-12	6,59E-13	0	5,68E-10	5,51E-13
HTP-nc	CTUh	5,23E-09	3,04E-11	1,66E-10	9,89E-11	3,95E-11	0	5,23E-09	3,04E-11
SQP	Dimensionless	1,59E+01	1,36E-02	4,25E-02	7,69E-02	1,62E-02	0	15,89637	0,013553

PM: Particulate matter emissions; **IRP:** Ionising radiation, human health; **ETP-fw:** Ecotoxicity (freshwater); **ETP-c:** Human toxicity, cancer effects; **HTP-nc:** Human toxicity, non-cancer effects; **SQP:** Land use related impacts / soil quality

Reading example: $9,0 \text{ E-}03 = 9,0 \cdot 10^{-3} = 0,009$

Classification of disclaimers to the declaration of core and additional environmental impact indicators

ILCD classification	Indicator	Disclaimer
ILCD type / level 1	Global warming potential (GWP)	None
	Depletion potential of the stratospheric ozone layer (ODP)	None
	Potential incidence of disease due to PM emissions (PM)	None
	Acidification potential, Accumulated Exceedance (AP)	None
ILCD type / level 2	Eutrophication potential, Fraction of nutrients reaching marine end compartment (EP-marine)	None
	Eutrophication potential, Accumulated Exceedance (EP-terrestrial)	None
	Formation potential of tropospheric ozone (POCP)	None
ILCD type / level 3	Potential Human exposure efficiency relative to U235 (IRP)	1
	Abiotic depletion potential for non-fossil resources (ADP-minerals&metals)	2
	Abiotic depletion potential for fossil resources (ADP-fossil)	2
	Water (user) deprivation potential, deprivation-weighted water consumption (WDP)	2
	Potential Comparative Toxic Unit for ecosystems (ETP-fw)	2
	Potential Comparative Toxic Unit for humans (HTP-c)	2
	Potential Comparative Toxic Unit for humans (HTP-nc)	2
Potential Soil quality index (SQP)	2	

Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Resource use

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
RPEE	MJ	1,51E+00	2,24E-03	1,09E+00	1,18E-01	2,68E-03	0	6,65E-02	-2,72E-01
RPEM	MJ	1,09E+00	0	-1,06E+00	0	0	0	-3,62E-02	0
TPE	MJ	2,60E+00	2,24E-03	3,72E-02	1,18E-01	2,68E-03	0	3,03E-02	-2,72E-01
NRPE	MJ	1,12E+01	3,95E-02	8,51E-01	2,13E-01	4,72E-02	0	1,60E+00	-9,90E-01
NRPM	MJ	1,97E+00	0	-5,74E-01	0	0	0	-1,39E+00	0
TRPE	MJ	1,32E+01	3,95E-02	2,77E-01	2,13E-01	4,72E-02	0	2,02E-01	-9,90E-01
SM	kg	1,94E-01	0	3,88E-03	0	0	0	0	0
RSF	MJ	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0
W	m ³	2,34E-03	2,53E-06	4,24E-04	1,13E-04	3,03E-06	0	5,13E-05	-2,62E-04

RPEE Renewable primary energy resources used as energy carrier; RPEM Renewable primary energy resources used as raw materials; TPE Total use of renewable primary energy resources; NRPE Non-renewable primary energy resources used as energy carrier; NRPM Non-renewable primary energy resources used as materials; TRPE Total use of non-renewable primary energy resources; SM Use of secondary materials; RSF Use of renewable secondary fuels; NRSF Use of non-renewable secondary fuels; W Use of net fresh water

Reading example: $9,0 \text{ E-}03 = 9,0 \cdot 10^{-3} = 0,009$

End of life - Waste

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
HW	kg	4,91E-07	1,89E-13	9,82E-09	1,85E-11	2,26E-13	0	1,04E-11	-1,34E-10
NHW	kg	1,24E-01	5,66E-06	2,42E-02	1,61E-04	6,77E-06	0	1,03E+00	-5,00E-04
RW	kg	2,85E-04	4,86E-08	7,67E-06	3,41E-05	5,82E-08	0	2,25E-06	-7,81E-05

HW Hazardous waste disposed; NHW Non-hazardous waste disposed; RW Radioactive waste disposed

Reading example: $9,0 \text{ E-}03 = 9,0 \cdot 10^{-3} = 0,009$

End of life – output flow

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
CR	kg	0	0	0	0	0	0	0	0
MR	kg	0	0	0	0	0	0	0	0
MER	kg	0	0	7,82E-02	0	0	0	0	0
EEE	MJ	0	0	0	0	0	0	0	0
ETE	MJ	0	0	0	0	0	0	0	0

CR Components for reuse; MR Materials for recycling; MER Materials for energy recovery; EEE Exported electric energy; ETE Exported thermal energy

Reading example: $9,0 \text{ E-}03 = 9,0 \cdot 10^{-3} = 0,009$

Information describing the biogenic carbon content at the factory gate

Biogenic carbon content	Unit	Value
Biogenic carbon content in product	kg C	0
Biogenic carbon content in the accompanying packaging	kg C	1,02E+00

Additional requirements

Greenhouse gas emission from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

National electricity grid	Unit	Value
Electricity, grid mix, Lithuania	kg CO ₂ -eq/kWh	4,12E-01

Additional environmental impact indicators required in NPCR Part A for construction products

In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-IOBC	kg CO ₂ eq.	1,40E+00	2,94E-03	7,39E-02	1,18E-02	3,58E-03	0	1,54E-02	-5,82E-02

GWP-IOBC Global warming potential calculated according to the principle of instantaneous oxidation.

Hazardous substances

The declaration is based upon reference to threshold values and/or test results and/or material safety data sheets provided to EPD verifiers. Documentation available upon request to EPD owner.

- The product contains no substances given by the REACH Candidate list or the Norwegian priority list.
- The product contains substances given by the REACH Candidate list or the Norwegian priority list that are less than 0,1 % by weight.
- The product contains dangerous substances, more than 0,1% by weight, given by the REACH Candidate List or the Norwegian Priority list, see table.
- The product contains no substances given by the REACH Candidate list or the Norwegian priority list. The product is classified as hazardous waste (Avfallsforskriften, Annex III), see table.

Indoor environment

The products covered by this EPD meet the legal requirements for stone wool thermal insulation.

Carbon footprint

Carbon footprint has not been worked out for the product.

Bibliography

ISO 14025:2010	Environmental labels and declarations - Type III environmental declarations - Principles and procedures
ISO 14044:2006	Environmental management - Life cycle assessment - Requirements and guidelines
ISO 21930:2007	Sustainability in building construction - Environmental declaration of building products
ISO 14040	EN ISO 14040:2009-11 Environmental management - Life cycle assessment - Principles and framework
EN 15804:2012+A2:2019	Sustainability of construction works - Environmental product declaration - Core rules for the product category of construction products
EN 12939:2000	Thermal performance of building materials and products – Determination of thermal resistance by means of guarded hot plate and heat flow meter methods – Products of high and medium thermal resistance
EN 12667:2001	Thermal performance of building materials and products – determination of thermal resistance by means of guarded hot plate and heat flow meter methods – products of high and medium thermal resistance
EN 13501-1:2007+A1:2009	Fire classification of construction products and building elements – part 1: Classification using data from reaction to fire tests
PCR	NPCR PART A Construction Products and Services
PCR	NPCR 012 Part B for Thermal Insulation Products.
CPR	Regulation (EU) No 305/2011 of the European parliament and of the council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC
CEN/TR 15941	Sustainability of construction works – Environmental product declarations – Methodology for selection and use of generic data; CEN/TR 15941:2010
DYNEA 2022	LCA results for 3 different binder data, results according EN 15884+A2, 2022
GaBi ts	GaBi ts dataset documentation for the software-system and databases, LBP, University of Stuttgart and Sphera, Leinfelden-Echterdingen, 2022 (https://www.gabi-software.com/support/gabi)
GHG 2022	Greenhouse gas conversion factors, https://www.gov.uk/government/publications/greenhouse-gas-reporting-conversion-factors-2022
Singh P, Goymann M, Goerke J	Background report for EPD of Paroc Stone Wool Insulation, January 2023.

	Program Operator	tlf	+47 23 08 80 00
	The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo Norway	e- post:	post@epd-norge.no
		web	www.epd-norge.no
	Publisher	tlf	+47 23 08 80 00
	The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo Norway	e- post:	post@epd-norge.no
		web	www.epd-norge.no
	Owner of the declaration	tlf	+358 46 876 8000
	Paroc Group Oy FI-00181, Helsinki, Finland	e- post:	InsulationEurope.Sustainability@owenscorning.com
		web	www.paroc.com
	Author of the life cycle assessment	tlf	+49 711 34 18 17-25
	Sphera Solutions GmbH Singh P, Goymann M, Goerke J	e- post:	info@sphera.com
		web	www.sphera.com
	ECO Platform ECO Portal	web web	www.eco-platform.org ECO Portal

EPD for the best environmental decision



Global
Program
Operator

